

Steam / Hot / Cold Water: Diesel Heated, Electric Motor

The **HX Series** combines the cleaning power of high pressure with the grease cutting effectiveness of hot water. The front mounted controls let you easily adjust the soap ratio and the temperature up to 250°F. The stainless steel panels and advanced features give years of trouble free service. A great piece of cleaning equipment anywhere electrical power is available and fast cleaning is needed.

PRESSURE	3500psi
FLOW CAPACITY	4.3gpm
OUTLET TEMP	Adjustable Temperature up to 250° F (170° rise)
POWER/ENGINE	10hp
VOLTS/PHASE/AMP	E3 is 208/230v / 3ph / 29amp, E4 is 460v / 3ph / 15amp
CONTROLS/SWITCHES	Hour meter, lighted on/off switches, adjustable temperature, panel mounted soap control
PUMP	Cat Pump - Oil Bath, Triplex, Ceramic Plungers, Brass head, Stainless Steel Valves
POWER DRIVE	Belt Drive
PRESSURE CONTROL	Regulator controlled, adjustable pressure wand, safety relief valve, safety burst disc
WATER SUPPLY	4 gallon float tank, double inlet filtration
PRESSURE HOSE	3/8" x 50' 250°F 5800psi, non-marking
GUN / WAND	48" molded insulator, adj. pressure wand with quick coupler
SOAP INJECTION	Inlet Chemical Injection at Full Pressure, Stainless Steel Chemical Metering Valve
NOZZLE	#4.5 (0°, 15°, 40°)
BURNER COIL	1/2" Schedule 80 4 Pancake High Efficiency Coil, Stainless Steel Enclosure
BURNER/POWER	Oil Fired, Forced Draft, Automatic Ignition, Fuel Solenoid, Fuel Filter with Water Separator
BURNER FUEL / CAP	Diesel fuel #1 or #2, Kerosene, Stove oil, JP8 fuel, 8 gallon capacity
FRAME CONSTRUCTION	Stainless steel frame, coil wrap and panels
WHEELS	4) 13" tires installed
NET WEIGHT/DIM.	509# 47" x 29" x 42"

*Specifications subject to change without notification and may vary due to ambient conditions

Featuring:

- ✓ **Instant Trigger Start (ITS):** The machine and burner starts and stops instantly when the trigger gun is pulled or released.
- ✓ **High Burner Output:** Provides the highest rise in water temperature in its class, even from the coldest water supply, with over 500,000 BTU.
- ✓ **Adjustable Controls for Multiple Applications:** The temperature and soap can easily be adjusted from the front mounted control knobs and the pressure is adjusted at the wand.
- ✓ **Steam Selection at Full Output:** Adjustable knob lets you select steam up to 250° F without the loss of flow, pressure or switching valves or nozzles.

Options...

Hose Reel, 3000psi (AR187), or 5000psi (AR188)

TO: _____

COMMENTS: _____

YOUR PRICE: _____

DISTRIBUTED BY: _____

