

SCU Series – Mobile Wash Skid 2 Gun, adjustable flow

Hot / Cold Water – Self Contained: Diesel Heated, Gas Engine

Experience ultimate duty cleaning power. The **SCU Series 2-gun** system has unbeatable water flow output and heat rise with 614,000 BTU's to get the job done much faster than comparable hot washers. The SCU Series has a rust proof, stainless steel frame and long lasting, quality components to withstand the daily use that a professional demands. The built-in generator has additional capacity to run lights or water recycle accessories and you can also carry water with the optional ProTowWash trailer for total self-containment.

PRESSURE	3000psi
FLOW CAPACITY	8.7gpm (two operators 4.3gpm ea.)
OUTLET TEMP	Panel Mounted Adjustable Thermostat to 200°F, 100°F Rise
POWER/ENGINE	27 hp Kohler, key start
ENGINE FUEL/CAP	Unleaded Gasoline, 8 gallons
CONTROLS/SWITCHES	Lighted On/Off switch, hour meter, adjustable temperature, soap control, aux. power, pressure gauge
PUMP	General Pump, oil bath, triplex ceramic plunger, brass head, stainless steel valves
POWER DRIVE	V-belt, low RPM-cooler, quieter, continuous duty performance. Easy Tension Rails
PRESSURE CONTROL	Adjustable pressure unloader, safety burst disc, flow switch, pressure switch, gauge
WATER SUPPLY	Minimum 25 gallon bulk supply tank required
PRESSURE HOSE	Qty 2) 3/8" x 50' double steel wire braid, 250°F rated, 5400psi, non-marking hose
GUN / WAND	Qty 2) 48" molded insulator wand with multi-nozzle holder and quick coupler
NOZZLE	Qty 2) #5 (15°, 40°)
SOAP INJECTION	Full pressure inlet soap injection, 8gal soap tank
BURNER COIL	1/2" sch 80 steel coil, 4 pancake, ceramic blanket insulation
BURNER/POWER	Wayne Oil Fired, 115v, Auto Ignition, Racor Fuel Filter w/Water Separator, Fuel Solenoid
BURNER FUEL/CAP	Diesel Fuel #1 or #2, Kerosene, 18 Gal. capacity for extended run time up to 8 hours
GENERATOR	On-board 2900 Watt, 115v generator for auxiliary power
CONSTRUCTION	All Stainless Steel: 1 1/4" tube frame, 14 gauge base, panels and coil wrap
WHEELS	Optional wheel kit available
WEIGHT/DIM	640#, 48" X 38" X 41"

Specifications subject to change without notification & may vary due to ambient conditions

Featuring...

- ✓ **Balanced unloader system** allows two operators to wash at the same time at full pressure.
- ✓ **Ultimate Duty:** More cleaning unit output than any other washer in standard production
- ✓ **Long run time** with 18 gal gasoline and diesel tanks to reduce down time
- ✓ **Rust Proof Construction** – stainless steel lifetime guarantee

Options...

Wheel kit w/ pull bar steering (AHB12), locking kit for wheel kit (AHB20), Hose Reel (AR425), Downstream injection kit (AC360), Antifreeze tank/valve-installed (AW008), Trailer, Tank Skid, Hydro Vacuum wastewater recovery

TO: _____

COMMENTS: _____

YOUR PRICE: _____

DISTRIBUTED BY: _____



ETL Listed
 Certified to UL 1776
 Certified to
 CAN/CSA B140.11

