

Steam / Hot / Cold Water – Self Contained: Diesel Heated, Gas Engine
 (*Q models are less than 80db @ 25')

Experience ultimate duty cleaning power. The **SCU Series** has the reserve horsepower and heat rise to get the job done faster, with less soap and reduced noise pollution. It has a rust proof, stainless steel frame and long lasting, quality components to withstand the daily use that a professional demands. The built-in generator has additional capacity to run lights and you can also carry water with the optional ProTowWash trailer for total self-containment.

PRESSURE	3500psi
FLOW CAPACITY	5.6gpm
OUTLET TEMP	Panel mounted adjustable temperature to 250°F (140° + rise)
POWER/ENGINE	630cc Honda
ENGINE FUEL/CAP	Unleaded gasoline, 8 gallons
CONTROLS/SWITCHES	Lighted on/off switches, hour meter, adj. thermostat, soap control, aux. power, pressure gauge
PUMP	General Pump
POWER DRIVE	V-belt, low RPM-cooler, quieter, continuous duty performance. Easy Tension Rails
PRESS. CONTROL	Total relief unloader, 0-5000psi gauge, safety burst disc, relief valve, pressure switch
WATER SUPPLY	3.5 Gal. float tank, double inlet filtration, 3 way inlet valve
PRESSURE HOSE	3/8" x 50' double steel wire braid, 250°F rated, 5400psi, non-marking hose
GUN/WAND	48" molded insulator wand with multi-nozzle holder and quick coupler
SOAP INJECTION	Full pressure inlet injection, metering valve, 8gal soap tank
NOZZLE	#6 (15°,40°) #5 (25° steam)
BURNER COIL	½" sch 80 steel coil, 4 pancake, ceramic blanket insulation, double wall stainless enclosure
BURNER/POWER	Oil Fired, 115v, Automatic Ignition, Racor Fuel Filter w/Water Separator, Fuel Solenoid
BURNER FUEL/CAP	Diesel Fuel #1 or #2, Kerosene, or fuel oil, 18 gallons
GENERATOR	On-board 2900 watt, 115v generator for auxiliary power
CONSTRUCTION	All Stainless Steel: 1¼" tube frame, 14 gauge base, panels and coil wrap
WHEELS	Optional wheel kit available
WEIGHT/DIMENSION	630#, 48"x38"x41"

Specifications subject to change without notification & may vary due to ambient conditions

Featuring...

- ✓ **Safe to use** flow sensitive unloader builds up pressure gradually to reduce gun recoil and relieve trapped pressure
- ✓ **More Standard Controls** incl. 3-way inlet valve, hour meter, pressure gauge, soap injection, lighted on/off switches, auxiliary power switch, and thermostat with steam.
- ✓ **Rust Proof Construction**-Stainless steel lifetime guarantee

Options...

Wheel Kit 13" w/ pull bar steering (AHB12), locking kit for wheel kit (AHB20), Hose Reel (AR425), Trailer, Tank Skid, if Hydro Vacuum wastewater recovery is needed, use RZV and a generator

TO: _____

COMMENTS: _____

YOUR PRICE: _____

DISTRIBUTED BY: _____



ETL Listed
 Certified to UL 1776
 Certified to
 CAN/CSA B140.11

