

HEAT LINK: HOT WATER GENERATOR; DIESEL FIRED

The **Heat Link** provides hot water cleaning capability to your existing cold-water washer. It is compact for portable use and requires very low power for the burner. The Heat Link is available as Diesel fired and 115V power supplies to meet your requirements.

TECHNICAL DATA	CPHL4
PRESSURE	Up to 3500psi
FLOW CAPACITY	3 – 4gpm
OUTLET TEMP	High Temp Switch
HEAT RISE	140° (100° @ 4gpm)
BURNER MOTOR	1/7 hp Motor
VOLTS/PHASE/AMPS	115v 1ph 2.5 amp
CONTROLS	On / Off Switch, Flow Switch Control, Burst Disc, Safety Relief Valve
PRESSURE HOSE	9 foot x 3/8" 5000psi hose
BURNER COIL	1/2" Sch 80 Dual Pass
BURNER	Diesel Fired Auto Ignition
BURNER INPUT/NOZZLE	238,000btu / 1.5 80B
FUEL CAPACITY	18 gallons
CONSTRUCTION	Stainless Steel Frame
WEIGHT/DIMENSION	280#, 36x17x33

*Specifications subject to change without notification and may vary due to ambient conditions.

Featuring:

- ✓ **Stainless Steel Construction:** All stainless steel frame and coil enclosure for lifetime corrosion resistance
- ✓ **High Efficiency Heater:** Durable schedule 80 steel coil provides a continuous source of hot water
- ✓ **Compact and Portable:** connects easily to your existing pressure washer

TO: _____

COMMENTS: _____

YOUR PRICE: _____

DISTRIBUTED BY: _____

